



CLASSIC SHERWOOD

Size: 600X148 mm | **Design:** Wood | **Finish:** Satin Matte Finish in Ceramic Floor Body | **Series:** Classic Wood



Front View



Scale View

Packaging Details

Size	No. of tiles in box	Coverege Area	
		sq/mtr	sq/ft
600X148 mm	10.0	0.89	9.56

Technical Specification

Sr.No.	Test Description	Standard Test Method	ISO 13006 : 2018	Nitco's Value	
			Specification Bia	600 mm side	148 mm side
1	Length and Width	ISO 10545-2 / EN 98	± 0.3 % (Max ± 1.0 mm)	± 0.15%	± 0.3%
2	Thickness	ISO 10545-2 / EN 98	± 5.0 % (Max ± 0.5 mm)	± 5.0%	
3	Straightness of sides	ISO 10545-2 / EN 98	± 0.3 % (Max ± 0.8mm)	± 0.13%	± 0.3%
4	Rectangularity	ISO 10545-2 / EN 98	± 0.3 % (Max ± 1.5 mm)	± 0.20%	± 0.3%
5	Surface flatness	ISO 10545-2 / EN 98			
	a. Centre curvature	ISO 10545-2	± 0.4 % (Max +1.8 mm)	± 0.20%	
	b. Edge curvature	ISO 10545-2		± 0.20%	± 0.40%
	c. Warpage	ISO 10545 - 2		± 0.20%	
6	Surface Quality	ISO 10545-2 / EN 98	95% free from visible defects	>95% free from visible defects	
7	Water Absorption	ISO 10545-3 / EN 99	3% < E 6%	< 6%	
8	Breaking Strength, N	ISO 10545-4 / EN 100	Min 1000 N	>1000 N	
9	Modulus of Rupture (MOR), N/mm ²	ISO 10545 -4 / EN 100	Min. 22	>22	
10	Abrasion Resistance (PEI III, IV, V)	ISO 10545-7 / EN 154	As Specified by Manufacture	As Specified	
11	Thermal Shock Resistance	ISO 10545-9 / EN 104	Resistant to 10 cycle	Resistant	
12	Crazing Resistance	ISO 10545-11 / EN 105	No Crazing	Resistant	
13	Resistance to Acids, Alkalies and Chemicals (Except HF Acid)	ISO 10545-13 / EN 106	No Visible effect	No Visible effect	

WANT TO GET IN TOUCH WITH US?

Toll Free: 1800 266 4826 | Email: marketing@nitco.in