

NITCO



Because every space is
UNIQUE

MARBILANO Series
600X1200MM GLAZED VITRIFIED TILES

Nitco presents Marbilano, a range of Glazed Vitrified Tiles with 2 premium designs namely, Bianco Marfil and Moon Crema. The designs are based on a simple design principle – to take grandeur to the next level in the most understated way. The gentle strokes and the minimalistic design patterns do just that. They create an impression so strong without really putting one off. Marbilano offers a choice of Full Polish (Glossy) and Sugar finish. Available in grand, monolithic canvas of 60x120cm, these tiles exude grandeur and charm unlike any other and combine a touch of never-seen-before class and the undeniable quality assurance from the house of Nitco.

Highest Breaking Strength | Anti Bacterial | High Gloss

Bianco Marfil

Random Phases



Available in Marbilano Gloss (Full Polish) Finish and Marbilano Sugar finish






Glossy Finish

Moon Crema



Random Phases



Available in Marbilano Gloss (Full Polish) Finish and Marbilano Sugar finish

MARBILANO Series
600X1200MM GLAZED VITRIFIED TILES

Technical Specifications GVT Tiles

(GROUP Bla EN 176 / ISO13006)

Sr. No.	Test Description	Test Method	ISO13006:2012E Specification	NITCO's Specification For 600x1200mm
1	Deviation in Length and Width	ISO 10545 - 2	± 0.6%	± 0.10%
2	Deviation in Thickness	ISO 10545 - 2	± 5.0%	± 4.0%
3	Straightness of sides	ISO 10545 - 2	± 0.5%	± 0.10%
4	Rectangularity	ISO 10545 - 2	± 0.6%	± 0.10%
5	Surface Flatness	ISO 10545 - 2	± 0.5%	± 0.15%
6	Water Absorption	ISO 10545 - 3	≤0.5% , Max 0.6%	< 0.5%
7	Modulus of Rupture (MOR), N/mm ²	ISO 10545 - 4	≥35	> 35
8	Breaking Strength, N	ISO 10545 - 4	≥1300 N	Min 2800
9	Abrasion Resistance	ISO 10545 - 7	PEI Group III, IV, V	As specified
10	Thermal Shock Resistance	ISO 10545 - 9	No Visible defects	Resistant
11	Crazing Resistance	ISO 10545 - 11	No Crazing	Resistant
12	Frost Resistance	ISO 10545 - 12	No visible damage	Resistant
13	Resistance to Acids, Alkalies and Chemicals (Except HF Acid)	ISO 10545 - 13	No visible Effect	Resistant
14	Resistance to Staining	ISO 10545 - 14	Min. 3	Class 4

Packing Details

Dimensions	Tiles / Box	Coverage Area/Box	
		Sq. Mtrs.	Sq. ft.
600mm x 1200mm	2	1.44	15.5

Corporate Office:

NITCO Ltd.,
NITCO House,
Sheth Govindram Jolly Marg,
Kanjur Marg (E),
Mumbai - 400042

Email: marketing@nitco.in
Web: www.nitco.in

Phone: +91-22-6752 1555
Fax: +91-22-6752 1500

To locate the nearest Exclusive NITCO Le Studio in your city
please call toll free no:1800 266 4826
or visit our Website: www.nitco.in



www.facebook.com/NitcoOfficial



www.twitter.com/nitcoltd



www.youtube.com/nitcolimited